

ACCESS KEYPAD



KPX2000 & RD26-C

SPECIFICATION

KPX2000

- Built in prox reader
- Input for separate Wiegand reader
- Uses EM cards or fobs
- 12VDC
- Selectable backlit feature
- Lock and aux outputs
- PCB formal coated

RD26-C

- High impact plastic reader for external use
- Fully encapsulated to IP65
- 9-12VDC @ max 50mA
- 26 bit EM formatted reader
- Wiegand 4 wire connections
- Card read time of 120ms
- Operating frequency: 125kHz

FEATURES

KPX2000

- Stylish design
- Audio key operation
- Door bell facility
- Single or dual modes using Aux output
- Individually programmable outputs
- Zinc alloy electroplated casing

RD26-C

- Small, compact design
- LED indication
- Weather resistant
- Simple wiring to controller
- Encapsulated electronics
- Choice of cards or fobs
- Compatible with Wiegand type controllers
- To work with the KPX2000

DIMENSIONS

KPX2000

- 120x76x25 (mm)
- 558g (Boxed) • 418g (Unboxed)

RD26-C

- 78x42x12 (mm)
- 86g (Boxed) • 58g (Unboxed)

CONTENTS

KPX2000

- 5 x Blue Fobs

RD26-C