

Fire tested range of maglocks and brackets from a market leader in access control

ARCHITECTURAL BRACKETS RGL SAFETY RANGE


FIRE TESTED to

BSEN1634-1-2014 & BS476:Part22:1987 (30, 60, 90 & 120 min timber door-sets)










BK1200-F-L/AB

SPECIFICATION

BK1200-F-L/AB

- · Specially designed bracket slots that allows for a simple one person installation of maglocks
- Fully adjustable brackets
- · Suitable for all RGL Standard Maglocks inc: ML1200 / ML1200-M



FEATURES

BK1200-F-L/AB

- · Fire rated (30, 60, 90 & 120 min timber door set)
- · L bracket for use on outward opening doors
- · ZL bracket for use on inward opening doors
- · Anodised aluminium finish
- · Z Bracket can provide an extra 20mm-30mm of reach for non standard door settings

If you are looking for alternative options, then please view the following bracket: Other bracket options: INWARD

· BK1200ZL (ZL Bracket)

- · ADJ1200-L (Highly adjustable L)
- · AH1200 (Required for Fire Doors)
- · BK1200L (L Bracket)

1201SM-1

EBNT/TF-1



OTHER PRODUCTS

TOUCH FREE

BK600-F-L/AB

DU-GB/PTE

DIMENSIONS

BK1200-F-L/AB

- · 265x72x45 (mm) L Bracket (LxWxD)
- · 265x60x60 (mm) Z Bracket (LxWxD) x2

3.74kg Boxed

Version 3.1

CONTENTS

BK1200-F-L/AB

- · L Bracket (1200lb)
- · 1 x ZL Brackets
- · 1 x Fixing kits
- · End caps





OUTWARD



+44 (0)1902 656667

www.rgl.co

info@rgl.co