

DOUBLE ARCHITECTURAL 1200 BRACKETS RGL SAFETY RANGE

FIRE TESTED to BSEN1634-1-2014 & BS476:Part22:1987 Fixing slots for hassle free installs (30, 60, 90 & 120 min timber door-sets) FIRE TESTED ed to BSEN16 .1.1.8.1.1. 'L' BRACKET MAGLOCK DOOR FRAME **NWARD** DOOR **BK1200-D-FL/AB SPECIFICATION FEATURES** BK1200-D-FL/AB

MAGNETIC LOO

Fire tested range of maglocks and brackets

BK1200-D-FL/AB

· Specially designed bracket slots that allows for a simple one person installation of double maglocks

- Fully adjustable brackets
- Suitable for all RGL Standard Maglocks inc: ML1200-D / ML1200-D-M

45mm 72mm 88m 60mn

- · Fire rated (30, 60, 90 & 120 min timber door set)
- · L bracket for use on outward opening doors
- · ZL bracket for use on inward opening doors
- · Anodised aluminium finish
- · Z Bracket can provide an extra 20mm-30mm of reach for non standard door settings

If you are looking for a non architectural finish, then please view the following bracket: • BK1200-D-ZL

OUTWARD

Other bracket options: • ADJ1200-L (Highly adjustable L) AH1200 (Required for Fire Doors) EBNT/TF-1 EXIT

BOLT

COVER

ADJUSTABLE FZ' BRACKET

WASHERS

ARMATURE



DIMENSIONS

BK1200-D-FL/AB · 530x72x45 (mm) L Bracket (LxWxD) · 265x60x60 (mm) Z Bracket (LxWxD) x2 3.74kg Boxed

> œ \checkmark

UKAS



- BK1200-D-FL/AB
- · Double L Bracket (1200lb)
- 2 x ZL Brackets
- · 2 x Fixing kits
- End caps



BK600-F-L/AB



Version 3.1

LRQA

CERTIFIED

ISO 9001

www.rgl.co